

EXPRESS YOUR SOUL

Collection 2014



progeo
ACTIVE DESIGN

EXELLE VARIO



Renewed and lightened, compact and elegant, Exelle Vario is equipped with a very functional system to swing the footplates inwardly/outwardly or simply remove them. Fully customisable with a wide range of colours and accessories available.

FRAME COLOURS

bright silver	polish black	bright orange	bright red	bright lime	bright Fuchsia	bright blue	bright anthracite	bright blue china	pearl white

SET COLOURS (REAR WHEELS AND FORKS)

TPOLOGY: Ultra light wheelchair with cross brace folding system for indoor and outdoor use. Product's technical data – see page 49



Extremely compact when folded.



Easy-to-operate footplate lock lever.



3 frame angles for the removable footplates: 95°



Removable and swing-away (inwardly/outwardly) footplates.



110°.



120°.

TECHNICAL DATA PROGED WHEELCHAIRS



JOKER



JOKER EVOLUTION



JOKER ENERGY



NOIR

TYPOLOGY	ULTRALIGHT RIGID (folding backrest)	ULTRALIGHT RIGID (folding backrest)	ULTRALIGHT RIGID (folding backrest)	ULTRALIGHT RIGID (folding backrest)
SEAT WIDTH	33 36 39 42 45 48 cm	33 36 39 42 45 cm	33 36 39 42 45 48 cm	33 36 39 42 45 cm
SEAT DEPTH	35 37.5 40 42.5 45 47.5 50 cm	35 37.5 40 42.5 45 47.5 cm	35 37.5 40 42.5 45 47.5 50 cm	35 37.5 40 42.5 45 47.5 cm
FOOTPLATE DISTANCE	from 35 to 54 cm (adjustable)	from 35 to 54 cm (adjustable)	made-to-measure	made-to-measure
BACKREST HEIGHT	from 24.5 to 47 cm (adjustable)	from 24.5 to 47 cm (adjustable)	from 24.5 to 47 cm (adjustable)	from 24.5 to 47 cm (adjustable)
BACKREST ANGLE	from 74° to 94° (adjustable)	from 74° to 94° (adjustable)	from 74° to 94° (adjustable)	from 74° to 94° (adjustable)
CAMBER	0° 2° 4°	0° 2° 4°	0° 2° 4° 8° 12°	0° 2° 4°
FRONT HEIGHT	from 40 to 56 cm (adjustable)	from 40 to 56 cm (adjustable)	from 36 to 54 cm (made-to-measure, NOT adjustable)	from 44 to 54 cm (made-to-measure, NOT adjustable)
REAR HEIGHT	from 38 to 46 cm (adjustable)	from 38 to 46 cm (adjustable)	from 36 to 52 cm (made-to-measure, NOT adjustable)	from 37 to 48 cm (made-to-measure, NOT adjustable)
FRONT FRAME ANGLE	Aluminium 85° 90° 100° Carbon 85° 90° 95°	Aluminium 85° 90° 100° Carbon 85° 90° 95°	made-to-measure	85° 90° 95°
TOTAL WIDTH	seat width + 17 cm (with 0° camber)	seat width + 17 cm (with 0° camber)	seat width + 17 cm (with 0° camber)	seat width + 17 cm (with 0° camber)
TOTAL LENGTH (standard configuration)	88 cm approx.	88 cm approx.	85 cm approx.	85 cm approx.
WHEELCHAIR'S WEIGHT (lightest configuration)	starting from 8.5 kg approx.	starting from 7.9 kg approx.	starting from 7.3 kg approx.	starting from 6.6 kg approx.
WEIGHT WITHOUT REAR WHEELS (lightest configuration)	starting from 5.9 kg approx.	starting from 5.3 kg approx.	starting from 4.7 kg approx.	starting from 4.0 kg approx.
MAXIMUM LOAD	125 kg	125 kg	140 kg	125 kg
ENCUMBRANCE (folded wheelchair)	---	---	---	---
TILT IN SPACE	---	---	---	---
POWER UNIT	---	---	---	---

ACCESSORIES AND OPTIONAL: consult the technical order form.

The technical data in this chart may change without notice.
Some data in this chart may depend on the final configuration of the wheelchair.

TECHNICAL DATA



EGO



TEKNA ADVANCE



YOGA



EXELLE



EXELLE VARIO

ULTRALIGHT FOLDING (seat and backrest)	ULTRALIGHT FOLDING (seat)	ULTRALIGHT FOLDING (seat and backrest)	ULTRALIGHT FOLDING (seat)	ULTRALIGHT FOLDING (seat)
33 36 39 42 45 48 cm	36 39 42 45 48 cm	36 39 42 45 cm	33 36 39 42 45 48 cm	33 36 39 42 45 48 cm
35 37.5 40 42.5 45 47.5 cm	35 37.5 40 42.5 45 47.5 cm	35 37.5 40 42.5 45 47.5 cm	35 37.5 40 42.5 45 47.5 cm	35 37.5 40 42.5 45 47.5 cm
from 35 to 54 cm (adjustable)	from 35 to 54 cm (adjustable)	from 35 to 54 cm (adjustable)	from 32 to 51 cm (adjustable)	from 32 to 51 cm (adjustable)
from 24.5 to 47 cm (adjustable)	from 24.5 to 47 cm (adjustable)	from 24.5 to 47 cm (adjustable)	from 30 to 54 cm (adjustable)	from 30 to 54 cm (adjustable)
from 78° to 94° (adjustable)	84° 90° 96° (adjustable)	4 possible angles	Standard frame 90° Dynamic frame from 81° to 99°	Standard frame 90° Dynamic frame from 81° to 99°
0° 2°	0° 2° 4°	0° 2°	Standard frame 0° 1.5° 3° Dynamic frame 0° 1.5° 2° 4°	Standard frame 0° 1.5° 3° Dynamic frame 0° 1.5° 2° 4°
from 40 to 58 cm (adjustable)	from 40 to 58 cm (adjustable)	from 43 to 53 cm (adjustable)	from 39 to 58 cm (adjustable)	from 39 to 58 cm (adjustable)
from 38 to 45 cm (adjustable)	from 38 to 46 cm (adjustable)	from 41 to 49 cm (adjustable)	from 38 to 51 cm (adjustable)	from 38 to 51 cm (adjustable)
Aluminium 85° 90° 100° Carbon 85° 90° 95°	90° 100°	90° 100°	100° 110°	95° 110° 120°
seat width + 17 cm (with 0° camber)	seat width + 17 cm (with 0° camber)	seat width + 17 cm (with 0° camber)	seat width + 17 cm (with 0° camber)	seat width + 17 cm (with 0° camber)
88 cm approx.	88 cm approx.	90 cm approx.	90 cm approx.	90 cm approx. (70 cm without footplates)
starting from 9.8 kg approx.	starting from 10.2 kg approx.	starting from 12.2 kg approx.	starting from 9.5 kg approx.	starting from 10.6 kg approx.
starting from 7.2 kg approx.	starting from 7.6 kg approx.	starting from 9.6 kg approx.	starting from 6.9 kg approx.	starting from 8.0 kg approx.
125 kg	125 kg	125 kg	125 kg	125 kg
28 cm approx. (with 0° camber)	28 cm approx. (with 0° camber)	28 cm approx. (with 0° camber)	26 cm approx. (with 0° camber)	26 cm approx. (with 0° camber)
---	---	---	---	---
---	---	---	---	---

ACCESSORIES AND OPTIONAL: consult the technical order form.

TECHNICAL DATA PROGEO WHEELCHAIRS



BASIC LIGHT



TEKNA TILT ADULT



VARIOTRONIC

TYPOLOGY	LIGHT FOLDING (seat)	TILTING FOLDING (seat and backrest)	ELECTRONIC AND MANUAL
SEAT WIDTH	36 39 42 45 48 51 54 cm	33 36 39 42 45 48 cm	36 39 42 45 48 cm
SEAT DEPTH	40 42.5 45 cm (adjustable)	37.5 40 42.5 45 47.5 50 cm	35 37.5 40 42.5 45 47.5 cm
FOOTPLATE DISTANCE	from 30 to 52 cm (adjustable)	from 27 to 50 cm (adjustable)	from 32 to 51 cm (adjustable)
BACKREST HEIGHT	from 27 to 47 cm (adjustable)	from 35 to 72.5 cm (adjustable)	from 30 to 54 cm (adjustable)
BACKREST ANGLE	84° 90° 96° (adjustable)	from 78° to 102° (adjustable)	90°
CAMBER	0°	0°	0°
FRONT HEIGHT	from 40 to 53 cm (adjustable)	from 39 to 50 cm with flat seat (adjustable)	49
REAR HEIGHT	from 38 to 53 cm (adjustable)	from 39 to 50 cm with flat seat (adjustable)	45
FRONT FRAME ANGLE	105°	Standard frame 95° Optional*: A 85° 90° 95° 100° B 95° 100° 105° 110° C da 100° a 165°	110° 120°
TOTAL WIDTH	seat width + 20 cm	Larghezza seduta + 20 (con ruote post. da 300 mm)	seat width + 20 cm manual vers. + 21 cm electronic vers.
TOTAL LENGTH (standard configuration)	97 cm approx.	95 cm approx. (75 cm without footplates)	electronic vers. 105 cm approx. manual vers. 95 cm approx. (75 cm without footplates)
WHEELCHAIR'S WEIGHT (lightest configuration)	starting from 15.8 kg approx.	starting from 17.5 kg approx.	electronic version starting from 65.0 kg approx. manual version starting from 13.0 kg approx.
WEIGHT WITHOUT REAR WHEELS (lightest configuration)	starting from 12.0 kg approx.	starting from 12.0 kg approx. (without footplates, rear wheels, armrests, antitippers)	manual version starting from 10.0 kg
MAXIMUM LOAD	125 kg	125 kg	125 kg
ENCUMBRANCE (folded wheelchair)	30 cm approx.	32 cm circa (con ruote posteriori da 300 mm)	29 cm approx.
TILT IN SPACE	---	0° 40°	---
POWER UNIT	---	---	width: 21cm + seat width length: 60cm height: 40cm weight without batteries: 23,5kg batteries weight :2 x 14,7kg

ACCESSORIES AND OPTIONAL: consult the technical order form.

The technical data in this chart may change without notice.

Some data in this chart may depend on the final configuration of the wheelchair.


TECHNICAL DATA



JOKER JUNIOR



EXELLE JUNIOR



JUNIOR LIGHT



TEKNA TILT JUNIOR

ULTRALIGHT RIGID (folding backrest)	ULTRALIGHT FOLDING (seat)	LIGHT FOLDING (seat)	TILTING FOLDING (seat and backrest)
27 30 33 36 39 cm	27 30 33 36 39 cm	27 30 33 36 cm	27 30 33 36 39 cm
30 32,5 35 37,5 40 cm	30 32,5 35 37,5 40 cm	30 32,5 35 37,5 cm	30 32,5 35 37,5 40 cm
from 15 to 50 cm (adjustable)	from 13 to 40 cm (adjustable)	from 18 to 40 cm (adjustable)	from 20 to 50 cm (adjustable)
from 24,5 to 47 cm (adjustable)	from 24,5 to 47 cm (adjustable)	from 27 to 47 cm (adjustable)	from 35 to 72,5 cm (adjustable)
from 74° to 94° (adjustable)	Standard frame 90° Dynamic frame from 81° to 99° (adj.)	90°	from 78° to 102° (adjustable)
0° 2° 4°	Standard frame 0° 1,5° 3° Dynamic frame 0° 1,5° 2° 4°	0°	0°
from 40 to 56 cm (adjustable)	from 39 to 58 cm (adjustable)	from 41 to 50 cm (adjustable)	from 39 to 50 cm with flat seat (adjustable)
from 38 to 46 cm (adjustable)	from 38 to 51 cm (adjustable)	from 38 to 47 cm (adjustable)	from 39 to 50 cm with flat seat (adjustable)
Aluminium 90° 100° Carbon 90° 95°	100°	100°	Standard 85° 90° (adj.) frame with swing away/removable footplates 85° 90° 95° 100° (adj.)
seat width + 17 cm (with 0° camber)	seat width + 17 cm (with 0° camber)	seat width + 17 cm (with 0° camber)	Larghezza seduta + 20 (con ruote post. da 300 mm)
75 cm approx.	75 cm approx.	80 cm approx.	90 cm approx. (70 cm without footplates)
starting from 8,5 kg approx.	starting from 10.2 kg approx.	starting from 13.0 kg approx.	starting from 16.5 kg approx.
starting from 5.9 kg approx.	starting from 7.8 kg approx.	starting from 9.7 kg approx.	starting from 11.0 kg approx. (without footplates, rear wheels, armrests, antitippers)
125 kg	125 kg	80 kg	125 kg
---	26 cm approx. (with 0° camber)	28 cm approx.	32 cm approx. (with 300 mm rear wheels)
---	---	---	0° 40°
---	---	---	---

ACCESSORIES AND OPTIONAL: consult the technical order form.

* optional frames: A = frame with adjustable angle; B = frame with adjustable angle and swing away/removable footplates ; C = frame with elevating footplates.

The company reserves to make changes and improvements without notice. It also reserves the right of total or partial reproduction. All wheelchairs shown in this catalogue are not necessarily photographed in standard configuration.

PROGEO by RehaTEAM s.r.l. Vicolo Negrelli 4, 31040 Castagnole di Paese TV ITALY - Tel. +39.0422.484657 r.a. / +39.0422.480387 - Fax +39.0422.484661 / +39.0422.484684 - info@rehateamprogeo.com - www.rehateamprogeo.com.

Company certified in compliance with the rules UNI EN ISO 9001. Product in compliance with CE rules



www.
rehateamprogeo.com

Graphic Project by © **DELINEODISIGN** COMUNICAZIONE
Printed by: Tipografia Faggionato
Printed in September 2013

Thanks by Milanocentrale



www.rehateamprogeo.com