


JOKER ENERGY



If you are looking for a rigid frame wheelchair that is manufactured solely for you, the answer is Joker Energy. A fully welded customised frame where only the backrest can be adjusted. The elliptical section tubing improves rigidness to an eye-catching designed, extremely light and compact wheelchair.



TYPOLOGY: Ultra light wheelchair with rigid frame for indoor and outdoor use. Product's technical data - see page 48

JOKER ENERGY



Carbon fibre mudguard.



New carbon fibre AIR backrest (optional), exclusive for the line of Progeo's rigid wheelchairs. It approximately keeps the weight characteristics of the version with upholstery and it allows all adjustments for a optimal posture.



Frame with adjustable footplate (optional).



Minimum encumbrance without rear wheels and folded backrest.



Fully welded frame, made-to-measure.

TECHNICAL DATA PROGEO WHEELCHAIRS









| | JOKER | JOKER EVOLUTION | JOKER ENERGY | NOIR |
|---|--|--|---|---|
| TYPOLOGY | ULTRALIGHT RIGID (folding backrest) | ULTRALIGHT RIGID (folding backrest) | ULTRALIGHT RIGID (folding backrest) | ULTRALIGHT RIGID (folding backrest) |
| SEAT WIDTH | 33 36 39 42 45 48 cm | 33 36 39 42 45 cm | 33 36 39 42 45 48 cm | 33 36 39 42 45 cm |
| SEAT DEPTH | 35 37.5 40 42.5 45 47.5 50 cm | 35 37.5 40 42.5 45 47.5 cm | 35 37.5 40 42.5 45 47.5 50 cm | 35 37.5 40 42.5 45 47.5 cm |
| FOOTPLATE DISTANCE | from 35 to 54 cm (adjustable) | from 35 to 54 cm (adjustable) | made-to-measure | made-to-measure |
| BACKREST HEIGHT | from 24.5 to 47 cm (adjustable) | from 24.5 to 47 cm (adjustable) | from 24.5 to 47 cm (adjustable) | from 24.5 to 47 cm (adjustable) |
| BACKREST ANGLE | from 74° to 94° (adjustable) | from 74° to 94° (adjustable) | from 74° to 94° (adjustable) | from 74° to 94° (adjustable) |
| CAMBER | 0° 2° 4° | 0° 2° 4° | 0° 2° 4° 8° 12° | 0° 2° 4° |
| FRONT HEIGHT | from 40 to 56 cm (adjustable) | from 40 to 56 cm (adjustable) | from 36 to 54 cm (made-to-measure, NOT adjustable) | from 44 to 54 cm (made-to-measure, NOT adjustable) |
| REAR HEIGHT | from 38 to 46 cm (adjustable) | from 38 to 46 cm (adjustable) | from 36 to 52 cm (made-to-measure, NOT adjustable) | from 37 to 48 cm (made-to-measure, NOT adjustable) |
| FRONT FRAME ANGLE | Aluminium 85° 90° 100° Carbon 85° 90° 95° | Aluminium 85° 90° 100° Carbon 85° 90° 95° | made-to-measure | 85° 90° 95° |
| TOTAL WIDTH | seat width + 17 cm (with 0° camber) | seat width + 17 cm (with 0° camber) | seat width + 17 cm (with 0° camber) | seat width + 17 cm (with 0° camber) |
| TOTAL LENGTH (standard configuration) | 88 cm approx. | 88 cm approx. | 85 cm approx. | 85 cm approx. |
| WHEELCHAIR'S WEIGHT (lightest configuration) | starting from 8.5 kg approx. | starting from 7.9 kg approx. | starting from 7.3 kg approx. | starting from 6.6 kg approx. |
| WEIGHT WITHOUT REAR WHEELS (lightest configuration) | starting from 5.9 kg approx. | starting from 5.3 kg approx. | starting from 4.7 kg approx. | starting from da 4.0 kg approx. |
| MAXIMUM LOAD | 125 kg | 125 kg | 140 kg | 125 kg |
| ENCUMBRANCE (folded wheelchair) | | | | |
| TILT IN SPACE | | | | |
| POWER UNIT | | | | |

ACCESSORIES AND OPTIONAL: consult the technical order form.

The technical data in this chart may change without notice. Some data in this chart may depend on the final configuration of the wheelchair.

TECHNICAL DATA











| | | | 100 July 100 | The second secon |
|--|---|---|--|--|
| EGO | TEKNA ADVANCE | YOGA | EXELLE | EXELLE VARIO |
| ULTRALIGHT FOLDING (seat and backrest) | ULTRALIGHT FOLDING (seat) | ULTRALIGHT FOLDING (seat and backrest) | ULTRALIGHT FOLDING (seat) | ULTRALIGHT FOLDING (seat) |
| 33 36 39 42 45 48 cm | 36 39 42 45 48 cm | 36 39 42 45 cm | 33 36 39 42 45 48 cm | 33 36 39 42 45 48 cm |
| 35 37.5 40 42.5 45 47.5 cm | 35 37.5 40 42.5 45 47.5 cm | 35 37.5 40 42.5 45 47.5 cm | 35 37.5 40 42.5 45 47.5 cm | 35 37.5 40 42.5 45 47.5 cm |
| from 35 to 54 cm (adjustable) | from 35 to 54 cm (adjustable) | from 35 to 54 cm (adjustable) | from 32 to 51 cm (adjustable) | from 32 to 51 cm (adjustable) |
| from 24.5 to 47 cm (adjustable) | from 24.5 to 47 cm (adjustable) | from 24.5 to 47 cm (adjustable) | from 30 to 54 cm (adjustable) | from 30 to 54 cm (adjustable) |
| from 78° to 94° (adjustable) | 84° 90° 96° (adjustable) | 4 possible angles | Standard frame 90° Dynamic framefrom 81° to 99° | Standard frame 90° Dynamic frame from 81° to 99° |
| 0° 2° | 0° 2° 4° | 0° 2° | Standard frame 0° 1.5° 3° Dynamic frame 0° 1.5° 2° 4° | Standard frame 0° 1.5° 3° Dynamic frame 0° 1.5° 2° 4° |
| from 40 to 58 cm (adjustable) | from 40 to 58 cm (adjustable) | from 43 to 53 cm (adjustable) | from 39 to 58 cm (adjustable) | from 39 to 58 cm (adjustable) |
| from 38 to 45 cm (adjustable) | from 38 to 46 cm (adjustable) | from 41 to 49 cm (adjustable) | from 38 to 51 cm (adjustable) | from 38 to 51 cm (adjustable) |
| Aluminium 85° 90° 100° Carbon 85° 90° 95° | 90° 100° | 90° 100° | 100° 110° | 95° 110° 120° |
| seat width + 17 cm (with 0° camber) | seat width + 17 cm (with 0° camber) | seat width + 17 cm (with 0° camber) | seat width + 17 cm (with 0° camber) | seat width + 17 cm (with 0° camber) |
| 88 cm approx. | 88 cm approx. | 90 cm approx. | 90 cm approx. | 90 cm approx. (70 cm without footplates) |
| starting from 9.8 kg approx. | starting from 10.2 kg approx. | starting from 12.2 kg approx. | starting from 9.5 kg approx. | starting from 10.6 kg approx. |
| starting from 7.2 kg approx. | starting from 7.6 kg approx. | starting from 9.6 kg approx. | starting from 6.9 kg approx. | starting from 8.0 kg approx. |
| 125 kg | 125 kg | 125 kg | 125 kg | 125 kg |
| 28 cm approx. (with 0° camber) | 28 cm approx. (with 0° camber) | 28 cm approx. (with 0° camber) | 26 cm approx. (with 0° camber) | 26 cm approx. (with 0° camber) |
| | | | | |
| | | | | |

ACCESSORIES AND OPTIONAL: consult the technical order form.

TECHNICAL DATA PROGEO WHEELCHAIRS







BASIC LIGHT

TEKNA TILT ADULT

VARIOTRONIC

| TYPOLOGY | LIGHT FOLDING (seat) | TILTING FOLDING (seat and backrest) | ELECTRONIC AND MANUAL |
|---|----------------------------------|---|--|
| SEAT WIDTH | 36 39 42 45 48 51 54 cm | 33 36 39 42 45 48 cm | 36 39 42 45 48 cm |
| SEAT DEPTH | 40 42.5 45 cm (adjustable) | 37.5 40 42.5 45 47.5 50 cm | 35 37.5 40 42.5 45 47.5 cm |
| FOOTPLATE DISTANCE | from 30 to 52 cm (adjustable) | from 27 to 50 cm (adjustable) | from 32 to 51 cm (adjustable) |
| BACKREST HEIGHT | from 27 to 47 cm (adjustable) | from 35 to 72.5 cm (adjustable) | from 30 to 54 cm (adjustable) |
| BACKREST ANGLE | 84° 90° 96° (adjustable) | from 78° to 102° (adjustable) | 90° |
| CAMBER | 0° | 0° | 0° |
| FRONT HEIGHT | from 40 to 53 cm (adjustable) | from 39 to 50 cm with flat seat (adjustable) | 49 |
| REAR HEIGHT | from 38 to 53 cm (adjustable) | from 39 to 50 cm with flat seat (adjustable) | 45 |
| FRONT FRAME ANGLE | 105° | Standard frame 95° Optional*: A 85° 90° 95° 100° B 95° 100°105° 110° C da 100° a 165° | 110° 120° |
| TOTAL WIDTH | seat width + 20 cm | Larghezza seduta + 20 (con ruote post. da 300 mm) | seat width + 20 cm manual vers. + 21 cm electronic vers. |
| TOTAL LENGTH (standard configuration) | 97 cm approx. | 95 cm approx. (75 cm without footplates) | electronic vers. 105 cm approx. manual vers. 95 cm approx. (75 cm without footplates) |
| WHEELCHAIR'S WEIGHT (lightest configuration) | starting from 15.8 kg approx. | starting from 17.5 kg approx. | electronic version starting from 65.0 kg approx. manual version starting from 13.0 kg approx. |
| WEIGHT WITHOUT REAR WHEELS (lightest configuration) | starting from 12.0 kg approx. | starting from 12.0 kg approx. (without footplastes, rear wheels, armrests, antitippers) | manual version starting from 10.0 kg |
| MAXIMUM LOAD | 125 kg | 125 kg | 125 kg |
| ENCUMBRANCE (folded wheelchair) | 30 cm approx. | 32 cm circa (con ruote posteriori da 300 mm) | 29 cm approx. |
| TILT IN SPACE | | 0° 40° | |
| POWER UNIT | | | width: 21cm + seat width length: 60cm height: 40cm weight without batteries: 23,5kg batteries weigth: 2 x 14,7kg |

 $\label{eq:accessories} \mbox{ACCESSORIES AND OPTIONAL: consult the technical order form.}$

The technical data in this chart may change without notice. Some data in this chart may depend on the final configuration of the wheelchair.

TECHNICAL DATA









| IOKED | JUNIOR |
|-------|--------|
| | |

EXELLE JUNIOR

JUNIOR LIGHT

TEKNA TILT JUNIOR

| JOKER JUNIOR | EXELLE JUNIOR | JUNIOR LIGHT | TEKNA TILI JUNIOR |
|---|--|---|--|
| ULTRALIGHT RIGID (folding backrest) | ULTRALIGHT FOLDING (seat) | LIGHT FOLDING (seat) | TILTING FOLDING (seat and backrest) |
| 27 30 33 36 39 cm | 27 30 33 36 39 cm | 27 30 33 36 cm | 27 30 33 36 39 cm |
| 30 32.5 35 37.5 40 cm | 30 32.5 35 37.5 40 cm | 30 32.5 35 37.5 cm | 30 32.5 35 37.5 40 cm |
| from 15 to 50 cm (adjustable) | from 13 to 40 cm (adjustable) | from 18 to 40 cm (adjustable) | from 20 to 50 cm (adjustable) |
| from 24.5 to 47 cm (adjustable) | from 24.5 to 47 cm (adjustable) | from 27 to 47 cm (adjustable) | from 35 to 72,5 cm (adjustable) |
| from 74° to 94° (adjustable) | Standard frame 90° Dynamic frame from 81° to 99° (adj.) | 90° | from 78° to 102° (adjustable) |
| 0° 2° 4° | Standard frame 0° 1.5° 3° Dynamic frame 0° 1.5° 2° 4° | 0° | 0° |
| from 40 to 56 cm (adjustable) | from 39 to 58 cm (adjustable) | from 41 to 50 cm (adjustable) | from 39 to 50 cm with flat seat (adjustable) |
| from 38 to 46 cm (adjustable) | from 38 to 51 cm (adjustable) | from 38 to 47 cm (adjustable) | from 39 to 50 cm with flat seat (adjustable) |
| Aluminium 90° 100° Carbon 90° 95° | 100° | 100° | Standard 85° 90° (adj.) frame with swing away/removable footplates 85° 90° 95° 100° (adj.) |
| seat width + 17 cm (with 0° camber) | seat width + 17 cm (with 0° camber) | seat width + 17 cm (with 0° camber) | Larghezza seduta + 20 (con ruote post. da 300 mm) |
| 75 cm approx. | 75 cm approx. | 80 cm approx. | 90 cm approx. (70 cm without footplates) |
| starting from 8,5 kg approx. | starting from 10.2 kg approx. | starting from 13.0 kg approx. | starting from 16.5 kg approx. |
| starting from 5.9 kg approx. | starting from 7.8 kg approx. | starting from 9.7 kg approx. | starting from 11.0 kg approx. (without footplastes, rear wheels, armrest antitippers) |
| 125 kg | 125 kg | 80 kg | 125 kg |
| | 26 cm approx. (with 0° camber) | 28 cm approx. | 32 cm approx. (with 300 mm rear wheels) |
| | | | 0° 40° |
| | | | |

 $\label{eq:accessories} \mbox{ACCESSORIES AND OPTIONAL: consult the technical order form.}$

^{*} optional frames: A = frame with adjustable angle; B = frame with adjustable angle and swing away/removable footplates; C = frame with elevating footplates.

The company reserves to make changes and improvements without notice. It also reserves the right of total or partial reproduction. All wheelchairs shown in this catalogue are not necessarily photographed in standard configuration.

PROGEO by RehaTEAM s.r.l. Vicolo Negrelli 4, 31040 Castagnole di Paese TV ITALY - Tel. +39.0422.484657 r.a. /+39.0422.484657 r.a. /+39.0422.484661 r.a. /+39.0422.484661 r.a. /+39.0422.484684 - info@rehateamprogeo.com - www.rehateamprogeo.com.

Company certified in compliance with the rules UNI EN ISO 9001. Product in compliance with CE rules



