



## Configuration

- Frame with height and backrest adjustment
- 20/24/26" Wheels and 75/100/125 mm front wheels
- Rubber slipcover or push rims with tetranops
- Knee lever brakes/extended brakes/scissor brakes
- Custom seat with an opening left/right/front/back/middle or no opening
- Backrest with canvas or upholstered and/or side support
- Push handles
- Armrests in different shapes and heights
- Custom upholstered armpads
- One or two-piece in height adjustable footrest
- Upholstered footrests
- Anti-tip system
- Adjustable headrest
- Pelvic belt
- Abduction bobbin
- Calf strap/calf protector
- Insertion rails for bedpan/toiletbucket
- Stainless steel bedpan/toiletbucket
- Other individual customisation

## Application possibilities

- Shower use
- Toilet use (roll-over)
- Self-propelled
- Independent transfers
- Hip width 48-54 cm
- Pressure ulcer prevention
- Incontinence prevention
- Reduced torso stability
- Hip angle restriction
- Scoliosis
- Limited arm and hand function
- Small knee angle
- Small or large ankle angle (equinus foot)
- Large body measurements
- Individual customisation

<b>Width wheelchair incl. wheels</b>	73-77 cm
<b>Seat width</b>	48-50-52-54 cm
<b>Seat height floor - top of the seat</b>	49-69 cm
<b>Length wheelchair ca.</b>	96 cm
<b>Weight wheelchair ca.</b>	23 kg
<b>Loadable weight</b>	150 kg
<b>Recommended distance: wall to toilet rim</b>	70 cm
<b>Toiletheight</b>	40-50 cm

*These specifications are only an indication and strongly depend on configuration and adjustment.*

Scan for the pre-fit form

