



Configuration

Frame with height and backrest adjustment
20/24/26" Wheels and 75/100/125 mm front wheels
Rubber slipcover or push rims with tetranops
Knee lever brakes/extended brakes/scissor brakes
Custom seat with an opening left/right/front/back/middle or no opening
Backrest with canvas/upholstered and/or side support
Push handles
Armrests in different shapes and heights
Custom upholstered armpads
One or two-piece in height adjustable or folding footrest
Upholstered footrests
Anti-tip system
Adjustable headrest
Pelvic belt
Abduction bobbin
Calf strap/calf protector
Insertion rails for plastic toiletbucket
Plastic toiletbucket
Other individual customisation

Application possibilities

- Shower use
- Toilet use (not roll-over)
- Self-propelled
- Independent transfers
- Hip width 30-36 cm
- Pressure ulcer prevention
- Incontinence prevention
- Reduced torso stability
- Hip angle restriction
- Scoliosis
- Limited arm and hand function
- Small knee angle
- Short leg length
- Amputation
- Individual customisation

Width wheelchair incl. wheels	55-60 cm
Seat width	30-32-34-36 cm
Seat height floor - top of the seat	47-56 cm
Length wheelchair ca.	79 cm
Weight wheelchair ca.	15 kg
Loadable weight	120 kg
Recommended distance: wall to toilet rim	N/A
Toiletheight	N/A

These specifications are only an indication and strongly depend on configuration and adjustment.

Scan for the pre-fit form

