



Configuration

Frame with height and backrest adjustment
20/24/26" Wheels and 75/100/125 mm front wheels
Rubber slipcover or push rims with tetranops
Knee lever brakes/extended brakes/scissor brakes
Custom seat with an opening left/right/front/back/middle or no opening
Backrest with canvas or upholstered and/or side support
Push handles
Armrests in different shapes and heights
Custom upholstered armpads
Height-adjustable, (comfort) legrests with folding footrests
Height-adjustable one-piece footrest
Upholstered footrests
Anti-tip system
Adjustable headrest
Pelvic belt
Abduction bobbin
Calf strap/calf protector
Insertion rails for bedpan/toiletbucket
Stainless steel bedpan/toiletbucket
Traveller frame (with suitcase) for travelling
Other individual customisation

Application possibilities

- Shower use
- Toilet use (roll-over)
- Self-propelled
- Independent transfers
- Hip width 40-46 cm
- Pressure ulcer prevention
- Incontinence prevention
- Reduced torso stability
- Hip angle restriction
- Scoliosis
- Limited arm and hand function
- Small or large knee angle
- Short or varying leg length
- Small or large ankle angle (Equinus foot)
- Amputation
- Differing body measurements
- Individual customisation

Width wheelchair incl. wheels 66-70 cm

Seat width 40-42-44-46 cm

Seat height floor - top of the seat 47-67 cm

Length wheelchair ca. 103 cm

Weight wheelchair ca. 20 kg

Loadable weight 120 kg

**Recommended distance:
wall to toilet rim** 70 cm

Toiletheight 40-50 cm

These specifications are only an indication and strongly depend on configuration and adjustment.

Scan for the pre-fit form

