



Configuration

Frame with height and backrest adjustment
20/24/26" Wheels and 75/100/125 mm front wheels
Rubber slipcover or push rims with tetranops
Knee lever brakes/extended brakes/scissor brakes
Custom seat with an opening left/right/front/back/middle or no opening
Backrest with canvas or upholstered and/or side support
Push handles
Armrests in different shapes and heights
Custom upholstered armpads
One or two-piece in height adjustable footrest
Upholstered footrests
Anti-tip system
Adjustable headrest
Pelvic belt
Abduction bobbin
Calf strap/calf protector
Insertion rails for bedpan/toiletbucket
Stainless steel bedpan/toiletbucket
Traveller frame (with suitcase) for travelling
Other individual customisation

Application possibilities

- Shower use
- Toilet use (roll-over)
- Self-propelled
- Independent transfers
- Hip width 40-46 cm
- Pressure ulcer prevention
- Incontinence prevention
- Reduced torso stability
- Hip angle restriction
- Scoliosis
- Limited arm and hand function
- Small knee angle
- Small or large ankle angle (equinus foot)
- Large body measurements
- Individual customisation

Width wheelchair incl. wheels	66-70 cm
Seat width	40-42-44-46 cm
Seat height floor – top of the seat	47-67 cm
Length wheelchair ca.	100 cm
Weight wheelchair ca.	20 kg
Loadable weight	120 kg
Recommended distance: wall to toilet rim	70 cm
Toiletheight	40-50 cm

These specifications are only an indication and strongly depend on configuration and adjustment.

Scan for the pre-fit form

