



## Configuration

Frame with height and backrest adjustment

20/24" Wheels and 100/125 mm front wheels

Rubber slipcover or push rims with tetranops

Knee lever brakes/extended brakes/scissor brakes

Custom seat with an opening left/right/front/back/middle or no opening

Backrest with canvas or upholstered and/or side support

Push handles

Armrests in different shapes and heights

Custom upholstered armpads

Height-adjustable, (comfort) legrests with folding footrests

Height-adjustable one-piece footrest

Upholstered footrests

Anti-tip system

Adjustable headrest

Pelvic belt

Calf strap

Insertion rails for bedpan/toiletbucket

Stainless steel bedpan/toiletbucket

Other individual customisation

## Application possibilities

- Shower use
- Toilet use (not roll-over)
- Tripping (propulsion with arms and/or legs)
- Hip width 40-46 cm
- Pressure ulcer prevention
- Incontinence prevention
- Reduced torso stability
- Hip angle restriction
- Amputation
- Differing body measurements
- Individual customisation

Width wheelchair incl. wheels 66-70 cm

Seat width 40-42-44-46 cm

Seat height floor – top of the seat 40-49 cm

Length wheelchair ca. 79 cm

Weight wheelchair ca. 16 kg

Loadable weight 120 kg

Recommended distance:  
wall to toilet rim N/A

Toiletheight N/A

*These specifications are only an indication and strongly depend on configuration and adjustment.*

Scan for the pre-fit form

