

**blue**



## Application possibilities

- Shower use
- Toilet use (roll-over)
- Hip width 40-46 cm
- Pressure ulcer prevention
- Incontinence prevention
- Reduced torso stability
- Hip angle restriction
- Scoliosis
- Small or large knee angle
- Short or varying leg length
- Small or large ankle angle (equinus foot)
- Amputation
- Differing body measurements
- Stationary use (without castors)
- Tripping propulsion
- Individual customisation

## Configuration

Frame with backrest adjustment
100/125 mm castors with brakes
Custom seat with an opening left/right/front/back/middle or no opening
Backrest with canvas or upholstered and/or side support
Push handles
Armrests in different shapes and heights
Custom upholstered armpads
Height-adjustable, (comfort) legrests with folding footrests
Height-adjustable one-piece footrest
Upholstered footrests
Adjustable headrest
Pelvic belt
Abduction bobbin
Calf strap/calf protector
Insertion rails for bedpan/toiletbucket
Stainless steel bedpan/toiletbucket
Other individual customisation

<b>Width wheelchair incl. wheels</b>	57 cm
<b>Seat width</b>	40-42-44-46 cm
<b>Seat height floor - top of the seat</b>	46-67 cm
<b>Length wheelchair ca.</b>	88 cm
<b>Weight wheelchair ca.</b>	16 kg
<b>Loadable weight</b>	120 kg
<b>Recommended distance: wall to toilet rim</b>	From 55 cm
<b>Toiletheight</b>	40-50 cm

*These specifications are only an indication and strongly depend on configuration and adjustment.*

Scan for the pre-fit form

