

compact

Self-propelled



Configuration

Frame with height and backrest adjustment
20/24" Wheels and 100/125 mm front wheels
Rubber slipcover or push rims with tetranops
Knee lever brakes/extended brakes/scissor brakes
Custom seat with an opening left/right/front/back/middle or no opening
Backrest with canvas or upholstered and/or side support
Push handles
Armrests in different shapes and heights
Custom upholstered armpads
Height-adjustable, (comfort) legrests with folding footrests
Upholstered footrests
Anti-tip system
Adjustable headrest
Pelvic belt
Abduction bobbin
Calf strap
Insertion rails for bedpan/toiletbucket/foldable bucket
Stainless steel bedpan/toiletbucket/foldable bucket
Suitcase for travelling (not all configurations fit completely in the suitcase)
Other individual customization

Application possibilities

- Shower use
- Toilet use (roll-over)
- Travelling (disassemblable)
- Self-propelled
- Independent transfers
- Hip width 40-46 cm
- Pressure ulcer prevention
- Incontinence prevention
- Reduced torso stability
- Hip angle restriction
- Scoliosis
- Limited arm and hand function
- Small or large knee angle
- Short or varying leg length
- Small or large ankle angle (equinus foot)
- Amputation
- Differing body measurements
- Individual customisation

Width wheelchair incl. wheels	61-68 cm
Seat width	40-42-44-46 cm
Seat height floor - top of the seat	53-65 cm
Length wheelchair ca.	95 cm
Weight wheelchair ca.	21 kg
Loadable weight	120 kg
Recommended distance: wall to toilet rim	From 65 cm
Toiletheight	40-50 cm
Weight suitcase	5 kg
Measurements suitcase	H81 x W55 x D35 cm

These specifications are only an indication and strongly depend on configuration and adjustment.

Scan for the pre-fit form

